

**034N0084**

Refrigerants: HCFC and Non-flammable HFC refrigerants. Regulating range 0 - 6,0 bar (0 - 87 psig), factory setting 0,4 bar (5,8 psig), max. working pressure 28 bar (406 psig). Max. test pressure 31 ba...

> **Product specifications**
 > **Dimensions**
 > **Product labels (9)**
 > **Contact**

> **Code number selector**
 > **CAD Symbols (1)**
 > **Approvals & certificates (1)**



8+1 / 0

Characteristic	Value
Type	CPCE 22
Weight	0,850 Kg
Approval	C UL US LISTED, EAC
Approval file name	REFRIGERANT VALVE 53R0
EAN number	5702422020578
Inlet connection type	Solder
Inlet size [in]	7/8 in
Inlet size [mm]	22,00 mm
Max. Working Pressure [bar]	28,0 bar
Max. Working Pressure [psig]	392 Psig
Outlet connection type	Solder
Outlet size [in]	7/8 in
Outlet size [mm]	22,00 mm
Pack format	Multi pack
Product description	Capacity Regulator
Product Group	Press. and temp. regul. valves
Product name	Hot gas bypass regulator
Quantity per pack format	8 pc
Rated capacity R134a [kW]	15,20 kW
Rated capacity R134a [TR]	8,40 TR
Rated capacity R22 [kW]	34,00 kW
Rated capacity R22 [TR]	12,20 TR
Rated capacity R404A/R507 [kW]	32,00 kW
Rated capacity R404A/R507 [TR]	12,10 TR
Rated capacity R407C [kW]	37,10 kW
Rated capacity R407C [TR]	13,20 TR
Refrigerant(s)	HCFC/HFC/HC
Regulation range [bar]	0,0 - 6,0 bar
Regulation range [psig] Pe	0,00 - 85,00 psig