



### 003N3100

Direct actuated valve.  
Refrigerants (condenser side):  
CFC, HCFC, HFC. Media (liquid  
side): fresh water, neutral  
brine. Media temperature  
range, WVFX 10-25: -25 -  
+130°C, WVFX 32-40:-25 -  
+90°C. Openin...

> **Product specifications**

> **Product labels (4)**

> **Contact**

> **Code number selector**

> **Approvals & certificates (1)**



8+1 0

Characteristic	Value
Type	WVFX 20
Weight	1.17 Kg
Approval	EAC
Body material	BRASS
Connection	G 3/4
Connection Internal/External	Internal
Connection size (refrigerant)	1/4 in - 6 mm
Connection standard	ISO 228-1
Connection type (refrigerant)	SAE flare
Control pressure range [bar]	3,50 - 16,00 bar
Cv value [gal/min]	3,900 gpm US
EAN number	5702422042488
Kv value [m <sup>3</sup> /h]	3,400 m <sup>3</sup> /h
Max. pressure drop [bar]	10 bar
Max. pressure drop [psi]	145 psi
Max. Working Pressure [bar]	16,0 bar
Max. Working Pressure [psig]	232 Psig
Media	Fresh water
Media	Neutral brine
Medium temperature range [°C]	-25 - 130 °C
Medium temperature range [°F]	-13 - 266 °F
Max. Working Pressure (refrigerant) [bar]	26,4 bar
Orifice size [mm]	20,00 mm
Pack format	Multi pack
Product description	Water valve
Product Group	Water regulating valves
Product name	Water Regulating valve
Quantity per pack format	10 pc
Refrigerant(s)	HCFC/HFC/HC