


NEK2150U



**ENGINEERING CODE**  
863NA51



**REFRIGERANT**  
R-290



**POWER SUPPLY**  
220-240 V 50 Hz



**APPLICATION**  
LBP



**MOTOR TYPE**  
CSIR



**STANDARD**  
EN12900



**COOLING CAPACITY**  
325 W



**EFFICIENCY**  
1.05 W/W



DATA

GENERAL DATA

Model	NEK2150U
Type	Hermetic Reciprocating
Technology	ON/OFF
Compressor Application	LBP
Expansion Device	Capillary Tube or Expansion Valve
Compressor Cooling	Fan/220
HP	1/2
Starting Torque	HST
Plant	SLOVAKIA

ELECTRICAL DATA

Start Winding Resistance	19.29 Ω at 25°C
Run Winding Resistance	5.98 Ω at 25°C

## MECHANICAL DATA

Displacement	13.54 cm <sup>3</sup>
Oil Charge	350 ml
Oil Type	AB
Oil Viscosity	ISO32
Weight	11.6 Kg

## ELECTRICAL COMPONENTS

Start Capacitor	64-77 µf/330 V
CSR CSIR BOX	No
Starting Device Type	RELAY
Starting Device Description	MTRP-0029*
Overload Protection	MSP30APK-3259

## PERFORMANCE

### TESTED CONDITIONS

Tested Refrigerant	R-290
Tested Application	LBP
Tested Standard	EN12900
Tested Cooling	Fan
Tested Voltage	220 V
Refrigerant Temperature	Dew

### RATED POINTS

Condensing Temperature °C	Evaporating Temperature °C	Cooling Capacity W	Efficiency W/W	Power Consumption W	Current A	Gas Flow Rate kg/h
40	-35	325	1.05	311	-	3.73

Test Condition: Subcooling 0 K, Return Gas 20 °C. Data are an indication of performance based simulation.

### PERFORMANCE CURVE

Condensing Temperature 35°C

Evaporating Temperature °C	Cooling Capacity W	Efficiency W/W	Power Consumption W	Current A	Gas Flow Rate kg/h
-40	267	0.99	269	-	2.92
-35	348	1.14	304	-	3.82
-30	450	1.32	341	-	4.96
-25	576	1.53	377	-	6.36
-20	726	1.76	412	-	8.05
-15	901	2.03	443	-	10.04
-10	1102	2.35	469	-	12.35

Test Condition: Subcooling 0 K, Return Gas 20 °C. Data are an indication of performance based simulation.

## PERFORMANCE CURVE

Condensing Temperature 45°C

Evaporating Temperature °C	Cooling Capacity W	Efficiency W/W	Power Consumption W	Current A	Gas Flow Rate kg/h
-40	233	0.83	279	-	2.79
-35	302	0.95	317	-	3.63
-30	391	1.09	359	-	4.72
-25	500	1.24	404	-	6.06
-20	630	1.40	450	-	7.67
-15	783	1.58	496	-	9.58
-10	959	1.78	539	-	11.80

Test Condition: Subcooling 0 K, Return Gas 20 °C. Data are an indication of performance based simulation.

## PERFORMANCE CURVE

Condensing Temperature 55°C

Evaporating Temperature °C	Cooling Capacity W	Efficiency W/W	Power Consumption W	Current A	Gas Flow Rate kg/h
-30	327	0.88	372	-	4.40
-25	420	0.99	423	-	5.67
-20	531	1.11	478	-	7.21
-15	662	1.24	535	-	9.03
-10	813	1.37	593	-	11.16

Test Condition: Subcooling 0 K, Return Gas 20 °C. Data are an indication of performance based simulation.

## ENVELOPE




## External

### EXTERNAL CHARACTERISTICS


Base Plate		SMALL	
Tray Holder		NO	
<b>Connector</b>	<b>Internal Diameter</b>	<b>Shape</b>	<b>Material</b>
Suction	8.1 mm	SLANTED 42°	COPPER
Discharge	6.1 mm	STRAIGHT	COPPER

EXTERNAL DIMENSIONS

SHELL



BASE



FENCE

